12 Dets

EPA-R6-2013-010211

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY 6608 Hornwood Drive Houston, Texas 77074 SUBJECT: Transmittal Memo - Compliance Monitroing Report(s) Inspector FROM: Director, S&A Division, 6ASA THRU: Chief, Field Operations Section, Houston Branch, 6ASA THRU: Chief, Houston Branch, 6ASAH WAR N A compliance Monitoring inspection was conducted on Dec. 23 FO at the following location: NAME: Koppers Co., Inc., Organic Materials Group ADDRESS: Old Industrial Road, ARMCO Steel Gate #1, Houston, Tex. AQCR: NPDES Permit #: Federal [] Municipal [] Non-Municipal Type of Facility: Compliance Monitoring Reports Attached: (Check appropriate space) Air 0&M SPCC TSCA -RCRA Water Form 7500-5 [] [] Γ٦ 1 and SIP **NPDES** Form 3560-3 NSPS Preliminary NSR Мајо PSD Assess ment Minor NESHAP [NOD Demo. T CEI CSI 129 PP Bioassay Salmonella **PCB** Comments: The plant staff is apparently unfamiliar with much of RCRA's regulations; relying heavily on corporate developed compliance preparations which are largely incomplete at the time Apparent violations include the following: Manifest system only partially in compliance B) Marking + placarding of containers used for storage-shipping was inadequate a containers No training plan yet developed for personnel handling harardous wastes @ No waste analysis plan yet been prepared. EPA Form 1320-6 (Rov. 6-72) (No written inspection schedule yet been prepared. (No written operating record yet been started.

RCRA SITE INSPECTION ACTIVITY REPORT:

2 9 DEC 1980

Facility (Name & Location):	Kopper	s Co. Inc.			: .
Type of Facility: Gen.	. ,,	Gen/TSD_	-	TSD	
Inspector (Name): 6/enn	A. St	inkis			-
Date of Inspection: Dec.	23,	1980			
Time of Inspection: From:	7		1545	Hours	
Pre-Inspection Activities:				/ hours	
Administrative Preparation					
Entry to Facility					
Pre-Inspection Discussion					
Inspection Activities:				5 hours	
Waste Analysis Plan					
Contingency Plan					
Manifests, Records					
Sampling					
Post Inspection Activities:			_ 4	hours	
Post Inspection Discussion					
Report Preparation					
SUBTOTAL			10	hours	
TRAVEL:			2	hours	
FOTAL:				hours	

RCRA INSPECTION

. SITE IDENTIFICATION



A. Site Name		B. Street (or	other identifier)
Koppers Co., Inc., Organ	uc Materials	Troup ARMC	noustrial Road D. Stool Gato #1
c. City	D. State	E. Zip Code	F. County Name
Houston	Texas	77015	3/ 4
G. Site Operator Information			
1. Name (Same as A.)		2. Telephone (7/3) 4	Number 153-5446
3. Street 4	. City	5. State	6. Zip Code
P.O. Box 16150			
H. Site Description Distills coal Creosofe, put	tar (from a	oke ovens) to	produce
	in , enameis	, erc	
I. Type of Ownership			
	e3. Cou	nty 4.Munic	cipal <u>V</u> 5 Privat
J1. Generator2. Transp	porter <u></u> 3.Trea	tment4.Stora	ige5.Disposal
INSPEC	CTION INFORMATIO	N The state of the	
A. Principal Inspector Information			
1. Name Slem a Stantino 12,	124/80	2. Title	0 - 1 - 61
3. Organization		. Telephone No. (a	Operations Section
EPA Houston Branch		(713)226-5	
B. Inspection Participants John H. Walten baugh - Plant F	= 4 -	(3-) 200 31	
John "Al" Carnes - Asst, Plant			
Tordan Dern - S Environment		ppers G., Pitts bi	roh Pa
(Phme: (412)22	7-2207		J
			PIC

RCRA COMPLIANCE INSPECTION REPORT GENERATORS CHECKLIST

Sec	ction A - EPA Identification No.			
1.	Does Generator have EPA I.D. No.?	<u> </u> Yes	No	
	a. If yes, EPA I.D. No. TXD008089021			
Sec	tion B - Manifest			
1.	Does generator ship waste off-site?	Yes	_ No	
	a. If no, do not fill out Sections B and D.	· · · · · · · · · · · · · · · · · · ·		
	b. If yes, identify primary off-site facility(s) Use narra explanations sheet.) See pg. 5	ative		
2.	Does generator use Manifest?	Yes	No	
	a. If no, is generator a small quantity generator?	Yes	No-	NIA
	 If yes, does generator indicate this when sending waste to a T/S/D facility 	_ - Yes	No	A/A
	b. If yes, does manifest include the following information	1 ?		
	1. Manifest Document No.	1 Yes	No	
	2. Generators Name, Mailing Address, Telephone No.	1 Yes	No	
	3. Generator EPA I.D. No.	Yes	No	
	4. Transporter(s) Name and EPA I.D. No.	Yes	No	
	 5. a. Facility Name, Address and & EPA I.D. No. b. Alternate Facility Name, Address and EPA ID NO. c. Instructions to return to generator if undelive 	Yes Yes	No (No	see pg.s
	able?		<u>L</u> No	
	 Waste information required by DOT - Shipping name, quantity, (weight, or vol.) containers (type and number.) 	 ✓Yes	No	
	7. Emergency Information (optional) (special handling instructions, phone no.)		Yes 1	No

(8) Is the following certification on each manifest form?	YesNo
This is to certify that the above named materials are properly classified, desc packaged, marked and labeled and are in per condition for transportation accord the applicable regulations of the Depar of Transportation and the EPA.	ribed, pro- ing to
(9) Does Generator retain copies of Manifes	ts? Yes No
If yes, complete a through e. me dated 12	lioleo
a. (1) Did generator sign and date all manifest (2) Who signed for generator? Name L.M.	s? 1 Yes No
 b. (1) Did generator obtain handwritten signatured date of acceptance from initial transportance (2) Who signed and dated for transporter? Note that the signed is the signed and dated for transporter. 	ter? Yes No
c. Does generator retain one copy of manifest significant by generator and transporter?	gned Yes No
d. Do returned copies of manifest include facility operator signature and date of acceptance?	ty owner/ Yes No
e. Does generator retain copies for 3 years?	Yes No
Section C - Hazardous Waste Determination	
Does generator generate solid waste(s) listed in Su (List of Hazardous Waste)?	bpart D Yes No
a. If yes, list wastes and quantities $\frac{V-057}{K-035}$	Creosate spillage + sand
 Does generator generate solid waste(s) that exhibit characteristics? (corrosovity, ignitability, react EP toxicity) 	hazardous ivity,YesNo
a. If yes, list wastes and quantities (include EPA Hazardous Waste No.)	
b. Does generator determine characteristics by tes by applying knowledge of processes?	ting or Knowledge
 If determined by testing, did generator use methods in Part 261, Subpart C (or Equivale 	
 a. If equivalent test methods used, attach equivalent methods used. 	copy of

& Nome yet removed from WWTP, according to plant representative.

3.	Are there any other solid wastes generated by generators?	Yes No
	a. If yes, did generator test all wastes to determine non-hazardous characteristics?	Yes No
	 If no, list wastes and quantities deemed non-hazardous or processes from which non-hazardous waste was product (Use additional sheet if necessary.) 	s ced?
i i i i i i i i i i i i i i i i i i i	Pitches, Enamels (spills + sand) ~ 700	Cu Yd/Yr.
	- Frash (i.e. wood, paper, empty dryms) =	
Sec	ction D - Pre-Transport Requirements	
1.	Does Generator package waste in accordance with 49 CFR 173 178, and 179? (DOT requirements)	✓Yes No
2.	a. Are containers to be shipped leaking or corroding? b. Use sheet to describe containers and condition. Contitue c. Is there evidence of heat generation from incompatible	Yes No was O.K.
	wastes in the containers?	Yes V No
3.	Does the generator use DOT labeling requirements in accordance with 49 CFR 172?	YesNo N/A
4.	Does the generator mark each package in accordance with 49 CFR 172?	Yes X No
5.	Is each container of 110 gallons or less marked with the following label?	
	Label saying: <u>HAZARDOUS WASTE</u> - Federal Law Prohibits Improper Disposal. If found, contact the nearest policy or public safety authority or the U.S. Environmental Pro- tection Agency.	
	Generator's Name and Address	
	Manifest Document Number	
6.	Does generator have placards to offer to transporters?	Yes _ No } See pg.
7.	Accumulation Time	
	a. Are containers used to temporarily store waste before transport? (w/odmir) See P9.5	✓Yes No}

 If yes, is each container clearly dated? Also, fill out rest of No. 7 (Accum. Time) 	YesNo
 b. 1. Does generator inspect containers for leakage or corrosion? (265.174 - inspections) 2. If yes, with what frequency? 	Yes No When brought into
c. Does generator locate containers holding ignitable or reactive waste at least 15 meters (50 feet) from the facility's property line? (265.176 - Special Requirements for Ignitable or Reactive Wastes)	= Yes No. N/
NOTE: If tanks used, fill out checklist for tanks. Wustewalk d. Are the containers labeled and marked in accordance with Section D 3, 4, & 5 of this form?	Treatment Tanks (e., grit chambers, etc.) arily exempted as be 117/86. No N/
NOTE: If generator accumulates waste on-site fill out checklist for General Facilities, Subparts C and D. Fuelvded.	
 Does generator comply with requirements for personnel t (Attach checklist for 265.16 - Personnel Training). 	raining?YesNo
8. Describe storage area. Use photos and narrative explanation See pg. 6 and Abachment AA Section E - Recordkeeping and Records	sheet.
1. Does generator keep the following reports for 3 years?	
 a. Manifests and signed copies from designated facilities? b. Annual reports c. Exception Reports d. Test results 	Yes No W/A Yes No N/A Yes No N/A
 Where are records kept (at facility or elsewhere)? Who is in charge of keeping the records? Name Bannie B. 	Countity Office
Section F - Special Conditions	Supri
 Has generator received from or transported to a foreign source any hazardous waste? a. If yes, has he filed a notice with the Regional Administrator? b. Is this waste manifested and signed by Foreign consignee? c. If generator transported wastes out of the country has he received confirmation of delivered shipment? 	Yes No

FACI	LITY	 	
DATE		****	
EPA	ID NO.		

RCRA COMPLIANCE INSPECTION REPORT NARRATIVE EXPLANATIONS

SECTION B PART 1.6.
Solid wastes are shipped in a
metal bin by Browning - Ferric Co.
to their disposal facility at Calcasiew, Las
SECTION B PART 2.6.5.
Fealty name and address not shown in disposal
failety portion of manifest, but is specified in
generator's section of manifest. EPA I.D. number
for visposal failite not shown amountere on
for disposal facility not shown anywhere on manifest (as per shyment dated 12/10/20)
"我们是我们的我们是我们,我们是我们的时候是我们的,我们就是一个人的,我们就没有一个人的,我们也没有一个人的。""我们是我们的,我们就是我们的,我们就是我们的,
E) Transport, bin equipped with placards; however,
placard only on the 2 sides and
not the 2 ends as required by
DOT 172.504 table 2
7.)a.) Waste bins are metal boxes with flip up lovers.
7.)a.)Waste bins are metal boxes with flip up covers. (See photo in Atlantment AA). These boxes (motain ~ 20-25 yd.)

•	FALI	LIT	Υ	
	DATE		•,	and the second second
	EPA	ID	NO	

RCRA COMPLIANCE INSPECTION REPORT NARRATIVE EXPLANATIONS

SECTION	PART 8
(a) Waste transport le	ins are used to contain
spilled cressote (an	I other was lar fructions)
which has been y	mxed with sand at the spill site.
This mixture is	shoreled into wheelbarrows or
other receptacles a	nd then empteed into the bins
Bing are stored on	a increte slab.
SECTION	PART
SECTION	PART

RCRA COMPLIANCE INSPECTION REPORT 750 FACILITIES CHECKLIST

Section A - deneral ractifity Standards		
1. Does facility have EPA Identification No.?	Yes	_ No ·
A. If yes, EPA I.D. No. TXD00808902 If no, explain	1	
2. Has facility received hazardous waste from a foreign source?	Yes <u>/</u>	No
A. If yes, has he filed a notice with the Reg. Admin.	Yes	/ No/
Waste Analysis 3. Does facility maintain a copy of the waste analysis plan at the facility? (See btm. of pg. 7)	Yes L	No Ø
A. If yes, does it include(1) Parameters for which each waste will be analyzed?	Yes	10
(2) Test methods used to test for these parameters?	es	No No
(3) Sampling method used to obtain sample?	Yes	_ No
(4) Frequency with which the initial analysis will be reviewed or repeated?	Yes	_ w
(5) (for off-site facilities) Waste analyses that gener have agreed to supply?	rators Yes	No_ M
(6) (for off-site facilities) Procedures which are used inspect and analyze each movement of hazardous wast including: a. Procedures to be used to determine the identity of each movement of waste?	: e	-No- L

b. Sampling method to be used to obtain representative sample of the waste to be identified?	YesNo /
4. Does the facility provide adequate security through	
A. 24-hour surveillance system? (e.g. television monitoring or guards) at plant entrance OR	YesNo
B. (1) Artificial or natural barrier around facility (e.g. fence or fence and cliff)? Describe AND	Yes No
(2) Means to control entry through entrances (e.g. attendant, television monitors, locked entrance, controlled roadway access)? Describe	YesNo
General Inspection Requirements 5. Does the owner/operator maintain a written schedule at the facility for inspecting: (see btm. of pg.7) a. Monitoring equipment?	Yes No
b. Safety and emergency equipment?	Yes No
c. Security devices?	Yes VNo
d. Operating and structural equipment?	Yes No
e. Types of problems of equipment? 1. malfunction	Yes No
2. operator error	Yes No
3. discharges	Yes No

6. Does the owner/operator maintain an inspection log?	_Yes_	<u>I</u> No
A. If yes, does it include:		
(1) Date and time of inspection?	\ / es _	No
(2) Name of inspector?	Yes	No
(3) Notation of observations?	_Yes/_	No
(4) Date and nature of repairs or remedial action?	Yes _	No
B. Are there any malfunctions or other deficiencies not corrected? (Use narrative explanation sheet).	Yes_	No N/A
Personnel Training		
7. Does the owner/operator maintain Personnel Training Records at the facility? How long are they kept?	_ Yes <u>_\</u>	√No —
A. If yes, do they include:		
(1) Job title and written job description of each position?	Yes _	Ne
(2) Description of type and amount of training?	Yes_	No
(3) Records of training given to facility personnel?	Yes _	No
Requirements for Ignitable, Reactive or Incompatible Waste		
8. Does facility handle ignitable or reactive wastes?	Yes _	No
A. If yes, is waste separated and confined from sources of ignition or reaction, (open flames, smoking, cutting and welding, hot surfaces, frictional heat) sparks (static, electrical or mechanical), spontaneous ignition (e.g. from heat producing chemical reactions) and radiant heat?		
 If yes, use narrative explanations sheet to describe separation and confinement procedures. If no, use narrative explanation sheet to describe source of ignition or reaction. 	-Yes ≘s	No P/A

ues ignaceu j	and open flame confined to spec ocations? wes * parking areas		Ýes No
C. Are "No Smok	ing" signs posted in hazardous Not where bing place	areas?	les No
9. Check containers			
A. Are containe	rs leaking or corroding?	ΥΥ	esNo
. Ma21G2:	dence of heat generation from i	V	es No
Section B - Prepared	ess and Prevention		
1. Is there evidence the environment?	of fire, explosion or contami		es No
If yes, use narra	tive explanations sheet to exp	lain.	
2. Is the facility e	quipped with		
A. Internal comm	unication or alarm system?	LY	es No
(1) Is it ea	sily accessible in case of emer	gency?	es No
B. Telephone or personnel?	two-way radio to call emergency	response	es No
C. Portable fire spill control	extinguishers, fire control eq equipment and decontamination	uipment equipment?) Ve MoNE	es 1) No
(1) Is this operation	equipment tested to assure its n?		
D. Water of adequence spray system?	uate volume for hoses, sprinkle		es No
(1) Describe	source of water <u>Hess Ter</u>	mimal (neighb	poring pla

3. Is there sufficient aisle space to allow unobstructed movement of personnel and equipment?	∠ Yes	No
4. Has the owner/operator made arrangements with the local authorities to familiarize them with characteristics of the facility? (layout of facility, properties of hazardous waste handled and associated hazards, places where facility personnel would normally be working, entrances to roads inside facility, possible evacuation		
Touces.)	Yes _	No
5. In the case that more than one police and fire department might respond, is there a designated primary authority? a. If yes, list primary authority Houston Fire	Dept Yes_	No
6. Does the owner/operator have phone numbers of and agreements with State emergency response teams, emergency response contractors and equipment suppliers? Are they readily available to all personnel?	CIMA Tridustries pacti	the Channel Mutual Aid No No
7. Has the owner/operator arranged to familiarize local hospitals with the properties of hazardous waste handled and types of injuries that could result from fires, explosions, or releases at the facility?	Yes	No
8. If State or local authorities decline to enter, is this entered in the operating record?	Yes_	 No N/X
Section C - Contingency Plan and Emergency Procedures		
1. Is a contingency plan maintained at the facility?	Yes_ <u>_</u>	No
a. If yes, is it a revised SPCC Plan?	Yes_	No
2. Is there an emergency coordinator on site at all times? Distillation Supervisor	Yes	No -
Section D - Manifest System, Recordkeeping and Reporting		
Does facility receive waste from off-site?	Yes	No
a. If yes, does the owner/operator retain copies of all manifests?	- Voc	

(1) Are the manifests signed and dated and returned to the generator?	Yes	No
(2) Is a signed copy given to the transporter?	Yes _	No
2. Does the facility receive any waste from a rail or water (bulk shipment) transporter?	Yes _	∠No
a. If yes, is it accompanied by a shipping paper?	Yes _	N ⁄o
(1) Does the owner/operator sign and date the shipping paper and return a copy to the generator?	Yes Y	No
(2) Is a signed copy given to the transporter?	Yes _	No
 Has the owner/operator received any shipments of waste which were inconsistent with the manifest? (manifest discrepancies) 	Yes	<u>L</u> No
 a. If yes, has he attempted to reconcile the discrepancy with the generator and transporter? 1. If no, has Regional Administrator been notified? 	Yes Yes	No No
4. Does the owner/operator keep a written operating record at the facility? (See btm. of pg. 7)	Yes _1	No
A. If yes, does it include: (1) Description and quantity of each hazardous waste received?	Yes	No_N/4
(2) Location and quantity of each hazardous waste at each location?	Yes	No N/A
(3) Records and results of waste analyses?	Yes _	
(4) Reports of incidents involving implementing of the contingency plan?	Yes_	Mo

	(5) Records and results of required inspections?)
	(6) Monitoring, testing or analytical data? Yes No)
	(7) Closure cost estimates and for disposal facilities post-closure cost estimates? (Not effective until May 19, 1981.) YesNo	
5. Ha	s the facility received any waste (that does not come under e small generater exclusion) not accompanied by a manifest? Yes No	
a.	If yes, has he submitted an unmanifested waste report to the Regional Administrator?	_

Items designated in this manner indicate that
information was supplied the implector wer the plane
ly the company's headquarter's nenvironmental manager
Mr. Tordan Derm. Plant's staff apparently is unfamiliar
with much of RCRA's regulations and they depend in Corporate
developed compliance proparations. Many items not yet prepared.

NOTE: Applies to treatment in other than tanks, surface impoundments, and land treatment facilities.

1. Check treatment process and equipment:

	. Check treatment process and equipment:	
	a. Are there any leaks, corrosion or other failures evident?yes	√ ħo
		
2.	Is the process a continous feed system?yes	no
	a. If yes, is it equipped with a means to stop waste inflow (e.g. waste feed cut-off system or by-pass)? System Shutdown each weekend	no
3.	No sludge yet removed from treatment system	no N/M
4.	If a hazardous waste is received which is substantially different from any hazardous waste previously treated at the facility, are the following obtained?	-no-N/K
	a. Waste analyses and trial treatment tests (eg bench scale)? b. Written documented information on similar treatment of	_mo
	similar waste?	no
5.	Does the owner/operator inspect the following, where present?yes_	_no
	 a. At least daily. l. Discharge control and safety equipment (eg waste feed cut-off, by-pass, drainage or pressure relief systems)? 	no
	2. Data gathered from monitoring equipment (eg pressure and temperature gauges)?	-no
	 b. At least weekly. 1. Construction materials of treatment process or equipment to detect erosion or obvious signs of leakage? 	по
5.	Does the facility maintain a closure plan? (Effective May 19, 1981)	_110- N/A
7.	Are ignitable or reactive wastes placed in the treatment process?	
	yes • a. If yes, is the waste treated, rendered or mixed before or immediately after being placed in the treatment process	no
	so it no longer meets the definition of ignitable or reactive? - yes Describe or attach a copy of the treatment.	_no- N/,


WASTE PILES CHECKLIST

NOTE: Waste piles may also be managed as a landfill. 1. Is the pile containing hazardous waste protected from wind? ves no 50 Cu. Yd. of "creosote spillage + sand" mixture located inside dike at tank farm Is a representative sample of waste from each incoming shipment analyzed before the waste is added to the pile to determine the compatibility of the wastes? No wester being added but is being gradually havled away Does the analysis include a visual comparison of color and texture? No analysis being made Is the leachate or run-off from the pile considered a hazardous waste? (Effective November 19, 1981) a. If yes, is the pile managed with the following? (1) An impermeable base compatible with the waste? yes - no (2) Run on diversion? yes - no (3) Leachate and run-off collection? yes no or Is the pile protected from precipitation and run-on by some other means? 5. Are ignitable or reactive wastes placed in the pile? If yes, does the addition of the waste result in the waste or mixture no longer meeting the definition? (Use narrative explanation sheet to describe procedure) Is the waste protected from sources of ignition or reaction? — (1) If yes, use narrative explanations sheet to describe separation and confinement procedures. (2) If no, use narrative explanations sheet to describe sources of ignition or reaction. 6. Is the pile separated from other sources of reaction by a dike, berm or wall? ves 7. Is there evidence of fire, explosion, gaseous emissions, leaching or other discharge? (Use narrative explanation sheet) yes Ino

V.	UNITED STATE EN RONMENTAL PROTECTION DEN
ECT	6608 Hornwood Drive Houston, Texas 77074 Addendow IVED Transmittal Memo - Compliance Monitroing Report (A) DATE 391981
M:	Glenn Stankis , Inspector REGION 6 S&A DIV.
	Director, S&A Division, 6ASA
	THRU: Chief, Field Operations Section, Houston Branch, 6ASAHF LAS (1/2/81)
	THRU: Chief, Houston Branch, 6ASAH DHP for
	A compliance Monitoring inspection was conducted on 12/23/80 at the following location: (Dates)
	NAME: Koppers Co., Inc. (ARMCO Steel Co. Gate #1)
•	ADDRESS: Houston, Texas
•	NPDES Permit #: AQCR: 216
	Type of Facility: Federal [] 'Municipal [] Non-Municipal [] Addexdvm Compliance Monitoring Reports Attached: (Check appropriate space)
	Water Air 08M SPCC TSCA RCRA
	NPDES [] SIP [] Form 7500-5 [] [] [] Form 3560-3 [] NSPS [] Majo [] NSR [] Minor [] PSD [] NOD [] NESHAP [] CEI [] Demo. [] CSI [] Bioassay [] Salmonella [] PCB []
	Comments:
	Photos taken during inspection - Attachment
100	
	hairing a de de de de Lorant
	Photos taken during inspection - Attachment A being sent as addendum to report Submitted earlier

Koppers Lo., The Quarter AN Koppers Lo., The Quarter ARMCO Steel Co. gate 4/ Houston, Texas Dec. 23 150 (RCRA Inspection)







UNITED STATES ENVIRONMENTAL PROTECTION AGENCY WASHINGTON, D.C. 20460

Region II

NOV 06 1984

OFFICE OF SOLID WASTE AND EMERGENCY RESPONSE

RE: WIBBB0622

Mr. Jordan M. Dern Manager, Environmental Regulatory Programs Koppers Company, Inc. Environmental Resources Department Pittsburgh, PA 15219

Dear Mr. Dern:

This letter is in response to delisting petition #0563 submitted by Koppers Company, Inc. of Houston, Texas for wastewater treatment sludges from the production of creosote, presently listed as EPA Hazardous Waste No. K035. I have reviewed the petition and have found that in addition to the analytical data which you intend to supply at a later date, several other points need to be addressed or clarified. Please supply the following information:

- Analyze at least four representative samples of the waste sludge for the following constituents: creosote, chrysene, naphthalene, fluoranthene, benz(b)fluoranthene, benz(a)pyrene, inden(1,2,3-cd)pyrene, benzo(a)pyrene, dibenzo(a)anthracene, and acenaphthalene. Include quality control data, the dates of sampling and analysis, the names and qualifications of the persons conducting the sampling and analysis, the method and equipment used to obtain the representative samples, a description of sample preparation and preservation techniques, the names and model numbers of all instruments used, and a description of the test methods used for each constituent. (If methods from SW-846 Test Methods for Evaluating Solid Waste are used, simply state the method numbers.)
- (2) Estimate the amount of total sludge that will be disposed. Will the amount continue to increase over time? (On page 3 of the petition, you estimated the amount of creosote in the sludge. We need to know the total amount of the sludge to be disposed.)
- (3) Provide a statement explaining why the samples you will collect will be representative of any constituent

concentration in the waste. I suggest you collect the samples in same manner as that described for the Follansbee, West Virginia facility, namely, collect several samples within a 24 hour period and composite into one sample.

(4) Hydrazine is listed as a constituent of Nalco 7274. It is been determined by the Carcinogen Assessment Group (CAG), to be a substance which poses a potential human cancer risk. It is also included on the Appendix VIII List of Hazardous Constituents in 40 CFR Part 261, and therefore, must be quantified in the waste. To determine the maximum amount of hydrazine present in the waste, samples may be analyzed by an appropriate analytical method or a mass balance may be computed as follows:

[(amount of hydrazine in the product) X (amount of product used within a time period)] / (amount of sludge produced in the same time period)

(5) The information contained on the Material Safety Data Sheet for Nalco 7309 was insufficient. What kind of organic degreasers are present in the product? If any of the constituents in the product are listed on Appendix VIII cited above, they should be quantified in a manner similar to that described for hydrazine.

You stated in the petition that in the future, you anticipate stabilizing the biological sludge with a dry material such as cement kiln before land disposal. If you still intend to pursue this method of treatment and disposal, the sludge samples analyzed for the delisting petition should be treated using the stabilization technique. According to the regulations, if the biological sludge was delisted, then underwent subsequent treatment, the product of the treatment would once again be considered hazardous. If you prefer that the waste be considered for delisting both before and after treatment, then submit data for the analysis of both stabilized and non-stablized waste.

I hope that this letter suficiently explains the additional information required. If you have any questions, please call me at (202) 382-4690.

Sincerely,

Buban L. Boot.

Barbara L. Bush

Environmental Protection Specialist Waste Identification Branch (WH-562)

Koppers Company, Inc. Environmental Resources Department Pittsburgh, PA 15219, Telephone 412-227-2000



KOPPERS

August 1,1984

Rect-1 8/7/84

Ms. Barbara Bush Waste Identification Branch Office of Solid Waste & Emergency Response United States EPA Washington, D. C. 20460

SUBJ: Koppers Co., Inc.-Houston, Tx., EPA I.D.No.TXD008089021-Delist.Pet.

Dear Ms. Bush:

This petition is submitted in accordance with the requirements of 40 CFR 260.20 and 40 CFR 260.22 for the purpose of delisting a particular waste stream which is generated at the subject facility. Section 40 CFR 261.32, Hazardous Waste from Specific Sources, identifies "Wastewater Treatment Sludges from the Production of Creosote" as hazardous waste No. K035. After reviewing the background document which led to the listing of KO35 and comparing it to the waste stream which the Koppers' Houston Plant generates, we conclude that the wastewater treatment sludge which is produced at our facility is far different than the waste which the agency seeks to regulate. This petition requests that KO35 be delisted as a hazardous waste for the subject facility. Beside addressing the requirements of 40 CFR 260.22 we will also submit information which you requested from our Follansbee Plant in your letter of March 13, 1984 (WIBBB0126). Once this document is reviewed by your office we expect that you will advise us of the specific parameters for which the biological sludge needs to be analysed. We can then proceed to perform the analytical work. In this way we hope to expedite the delisting process as much as possible.

Koppers Company, Inc., operates a coal tar processing facility in Houston, Texas. Coal tar which is received from various coke manufacturers, is processed by distillation, extraction, and blending to produce a variety of products including industrial pitches, roofing products, and several grades of creosote. The wastewater which is generated is comingled with contaminated runoff and is treated before discharge to the Houston Ship Channel under TDWR Permit No. 01034 and NPDES Permit No. TX 0005096. Treatment operations include API separation, oil extraction, equalization, aeration (activated sludge), pH adjustment and activated carbon addition, and clarification.

The waste which is generated by the activated sludge process consists of waste biological organisms at a concentration of about 2% total suspended solids in treated effluent. The quantity of sludge to be wasted is a function of the organic loading on the system, the amount of activated carbon added and the efficiency of settling. Generally, the wastewater treatment plant operates as a "no waste" system, i.e., biological sludge is not intentionally removed from the treatment system. This phenomenon is generally due to low organic loading such that the sludge production is equal to the sludge removed from the system as Total Suspended Solids in the effluent in compliance with

the NPDES Permit. However, we may at some time in the future have to waste the biological sludge. We are taking steps now to delist the sludge to simplify future disposal.

Hazardous waste KO35 is evaluated in the Listing Background Document for "Creosote Production" which addresses both "Wastewater Treatment Sludges Generated in the Production of Creosote" and "Process Wastewater from Creosote Production". After reviewing this document we are convinced that the production sludges referred to in the Background Document are not the same as the waste biological sludge generated in our wastewater treatment system. In this regard we raise the following points:

1. Generation - Section II (c) of the background document Waste Generation and Management describes how the production sludge is generated. It states, "creosote wastewater is either discharged to publically owned treatment works (at smaller facilities) or treated on site in holding ponds (at larger plants). Where onsite treatment is utilized, ponds are dredged periodically, giving rise to the second listed waste stream. Based on the prevalent waste disposal practice in the chemical industry, these wastewater treatment sludges are transferred to a landfill for a final disposal. "

By comparison, our biological sludge is generated in a far different manner. Biological sludge is produced in an activated sludge wastewater treatment process. This process involves the aeration of the wastewater so that biological organisms can decompose the organic compounds into carbon dioxide and water. These microorganisms use the energy released in the decomposition reaction in combination with organics which are present to procreate additional microorganisms. The waste biological sludge which is produced is made up of the excess microorganisms formed in the activated sludge process. It is not as the result of allowing the wastewater to settle.

2. Concentration - Section I.3 of the background document estimates that 1,150 million pounds of creosote and 60 - 115 million pounds of production sludge are produced. Using the data that one pound of creosote is produced from 12 pounds of coal tar and that coal tar typically contains 1.5% water, the quantity of wastewater can be calculated from creosote production.

1,150 x 10^6 lbs creo x $\frac{12 \text{ lbs coal tar}}{1 \text{ lb.creo.}}$ x $\frac{1 \text{ gal.water*}}{2 \text{ gal.coal tar}}$ x $\frac{1 \text{ gal.coal tar}}{2 \text{ gal.coal tar}}$ x $\frac{1 \text{ gal.coal tar}}{2 \text{ gal.coal tar}}$ = $\frac{1 \text{ lb.creo.}}{2 \text{ gal.coal tar}}$

23.8 x 10⁶ gal.wastewater(average)
year

One can obtain the concentration of sludge in the wastewater by the following calculation:

 87.5×106 lbs.creo in sludge* x 1 gal.water x 106 ppm = 23.8×10^6 gal.wastewater 8.34 lbs.water

440,824 ppm creosote from production sludges in wastewater (average)

*average

Wastewater from production sludge has a creosote concentration of 440,000 ppm (44%). Our biological sludge on the other hand has a concentration of creosote components of less than 1 ppm (0.0001%). There is no rationale for these biological sludges to be regulated in the same manner as the production sludges.

It is also worthwhile to note that the background document on creosote production evaluated both "Wastewater Treatment Sludge from the Production of Creosote" and "Wastewater from the Production of Creosote" as hazardous wastes. The evaluation showed that the treatment sludges should be regulated as a hazardous waste and that the wastewater itself was not hazardous. Our biological sludge contains even less of these toxic compounds than the wastewater itself. Therefore, if the wastewater is not considered hazardous, our biological sludge should not be considered hazardous.

- 3. Management Practices In Section III A. 1.(a) of the background document a description of the holding pond is given. It states, "holding ponds may be sited in areas with highly permeable soils or they may lack adequate leaching control features. Further, there may be inadequate cover to impede migration of the waste constituents or inadequate flood control measures to impede washout in the event of heavy rain". It is obvious that the pond being described has natural sediments at the bottom. Our treatment, on the other hand, takes place in a steel tank and a concrete basin which effectively prevents the leaching of contaminants into the ground. The overflow from the basin is controlled to the plant outfall. If an unexpected buildup of biological organisms were to occur, it would be pumped back to the aeration basin. The chance of an uncontrolled overflow is virtually nil.
- 4. Ecological Effects We have analysed the biological sludge from this treatment unit as well as others that Koppers operates for three of the polynuclear materials included in the listing of hazardous constituents -- benzo(a)pyrene, benz(a)anthracene and benzo(b)fluoranthene and found that these constituents were present in concentrations of less than 1.0 mg/l. The biological

sludge, when subjected to the leachate test used for EP Toxicity, shows these compounds at less than detectable levels. This is not surprising in light of the observation made in the Background Document that polynuclear compounds are absorbed to sediments (in our case the biological organisms) very tightly and are not likely to be released from the sediments. Although there is little information on the concentrations of these compounds that constitute a hazard the fact that they are below the level of detection in the leachate would suggest minimal environmental impact.

In Section III. a 2 of the background document it is stated, "Since the waste constitutents include benzo(a)anthrance, benz(b)fluoranthene, and benzo(a)pyrene, and creosote which are known carcinogens, substantial environmental harm can result from exposure even in minute concentrations if mismanagement should occur." This statement in the Background Document has been reviewed by Donald J. McGraw, M.D., our Corporate Medical Director. His response is as follows:

"Pursuant to our discussion regarding the subject sludge and Koppers' application for delisting this material as hazardous waste, I would like to offer the following comments. First, I would concur that the constituents of creosote, benz(a)anthracene, benzo(b)fluoranthene and benzo(a)pyrene can be generated in the production of creosote and have at times been detectable in the wastewater treatment sludges from this process. And, these substances are included among those with potential carcinogenicity according to the CAG list. The scientific data available to date, however, do not support the concept that there is an absolute no threshold health effect related to exposure to these compounds. Various PAH's are so pervasive, even ubiquitous, in most Western communities as to deny the possibility of non-exposure to all but the most isolated rural dweller.

"Major sources of contamination include air, water and food, with air being the primary offender, and the respiratory system the avenue of entry upon which the majority of studies attributing carcinogenicity to exposure(s) are based. It has been estimated that the average daily airborne PAH exposure is in the range 0.1 to 1.0 micrograms. In water it is measurable in the .01 - .05 micrograms range, and in food from $1-10~{\rm ppb}~(1-10~{\rm micrograms})$. Smoking alone has been estimated to result in an average daily BaP exposure of 0.4 micrograms. If these levels were responsible for an excess of various cancers, it is likely that an epidemic would be visible, a situation not corroborated by the best appraisals of such world-renouned epidemiologists as Drs. Doll and Peto.

"In the absence of reliable dose response information for PAHinduced cancer in human beings, predictions of carcinogenic risk often devolve upon models for risk extrapolation. The least supportable of these is the linear one-hit model, and recent studies at the National Institute of Environmental Health Sciences, Biometry and Risk Assessment Program, suggest that nonlinear organ-specific kinetics may be more applicable (1). Certainly, considerable refinement of our current level of understanding these processes will be necessary before any assumptions can be rationally entertained with regard to human risk extrapolations. While it is a desirable objective to minimize unnecessary exposure to any potentially harmful substances, it does not seem reasonable to expect industry to achieve lower than ambient environmental levels. The concentrations of these substances in the Follansbee waste water treatment sludge *are at barely detectible levels and do not, consequently, represent a potential for "substantial environmental harm" as suggested by the language in the Federal Listing Background Document."

"Furthermore, the National Academy of Science (NAS) Committee on Pyrene and Selected Analogues prepared a report on Polycylic Aromatic Hydrocarbons: Evaluation of Sources and Effects, which is due to be released soon. According to a summary in the July-August, 1983 NAS News Report, the Committee noted that about 99% of human exposure to PAH is from food and water, "presumably as a result of pollution from soils, irrigation waters, and atmospheric fallout and perhaps from the initial phases of food-processing." However, it added that there is "very little information to implicate diet derived PAHs in any form of clinical pathological condition, despite the high concentrations of these compounds to which humans may be exposed through food contamination."

*Data is not appreciably different for Houston Wastewater Treatment Sludge - JMD.

(1)"Implication of Non-Linear Kinetics on Risk Estimation in Carcinogenesis", David G. Hoel, et al., Science, Vol. 219, 4 March, 1983, pp. 1032 - 1037.

Our biological sludge is so different from production sludge in its 1) method of generation, 2) chemical characteristics 3) method of handling, 4) physical properties and 5) ecological effects that it should not be regulated as production sludge. While we recognize that it would be impossible for the Background Document to define every treatment scheme and every possible type of sludge, the vast difference between the production sludge and biological sludge makes it obvious that the writers of the Background Document did not intend to regulate waste biological organisms in the same manner that production sludges from holding ponds are to be regulated.

- 40 CFR 260.22 requires a review of the hazards associated with the waste. The criteria for the evaluation are given in 40 CFR 261.11 (a)(3). This section identifies 11 factors to evaluate whether the waste poses a "substantial present or potential hazard to human health or the environment". These will be considered in order.
- (i) Nature of Toxicity The Background Document identifies toxicity through virtually all routes for polynuclear materials, although there is relatively little data to identify the levels at which toxicity occurs. However, as the comments from Dr. McGraw point out polynuclear materials are nearly ubiquitous in our environment including air, water and food. Yet the absence of an excess of various cancers leads one to conclude the low concentrations of these polynuclear materials do not pose an unreasonable health risk.
- (ii) Concentration in the Waste This information will be determined in the next phase of the delisting process.
- (iii) Migration As the Background Document points out these compounds are not easily desorbed from the sediments (in this case the biological organisms). The same conclusion was reached in a study by Reichert, et.al, 1971 (2) which concluded that the reduction of PAH's in the wastewater was not due to biological degredation but to irreversible absorption of PAH's in the sludge.
- (iv) Persistence of the Constitutent This information is contained in the Background Document which states, "the polycylic aromatic hydrocarbons are persistent in nature, especially soils with half-lives for benzo(a)anthrancene and benzo(a)pyrene reported to be 7,000 and 21,000 hours, respectively."

⁽²⁾ Reichert, J., Hkunte, K.Engelhardt and J. Borneff (1971): Carcinogenic Substances Occurring in Water Soil - XXVII: Further Studies on the Elimination from Wastewater of Carcinogenic Polycylic Hydrocarbons". Archieves and Hygiene and Bakteriology. Vol. 155 Pg.18-40.

- (v) The potential to degrade Studies have shown that the organisms in soil will, after some time, attack and fracture the fused rings of the polynuclear compounds. One of the products of degradation will be phenol. However, since phenol is itself attacked by biological organisms, and since it is a "simplier compound" it will be more easily degraded. Thus it can be concluded that the degradation of creosote compounds will not generate other toxic products.
- (vi) Bioaccumulation Information in the Background Document suggests that polynuclear materials bioaccumulate in living organisms. However, more recent studies have shown that polynuclear compounds are metabolized to a variety of excretory products.(3) This would indicate that these compounds do not bioaccumulate to the extent previously thought.
- (vii) Types of Improper Management The only medium that could be adversely affected by the mismanagement of the waste would be groundwater. However, the low potential of the polynuclear materials to desorb from the sludge as demonstrated in the leachate analysis and the likelihood that any which is desorbed will be quickly reabsorbed by the sediments in the groundwater medium would lead one to conclude that the potential for harmful effects due to mismanagement are small.
- (viii) Quantities of waste generated At this time no waste biological sludge is being generated. When production levels increase, sludge wasting will likely be required. We wish to delist the waste now to simplify future disposal.
- (ix) Occurrence of human health and environmental damage To the best of our knowledge no human health of or environmental damage has occurred as a result of the mismanagement of this waste stream.
 - (x) Action by other regulatory agencies To the best of our knowledge no actions have been taken by any other regulatory agency.
- (xi) Such other factors All the pertinent information has been presented above. No other factors are known at this time.

⁽³⁾ A.W.Pucknat, Editor, <u>Health Impacts of Polynuclear Aromatic Hydrocarbons</u>, Park Ridge, New Jersey, 1981. Pg. 179.

We will address each item in your letter concerning our Follansbee Plant in order.

(1) Crude coke oven tar is the feedstock used to produce two major products for customer sales. They are creosote and a high softening point industrial pitch. There are two distillate fractions which are blended in varying proportions to produce the desired specification for the creosote.

The crude tar is pumped from storage to the dehydrator column where moisture is removed from the tar by pressurized vaporization. The water is condensed and processed through a decanter followed by the wastewater treatment plant. This wastewater stream gives rise to the designation of the biological sludge as a hazardous waste although the wastewater represents only a small part of the wastewater actually treated.

The dehydrated tar is then pumped to the distillation unit. Heat and vacuum are applied to produce a distillate stream called light creosote. Light creosote is a creosote stream which is relatively free of solids.

The bottoms stream from the distillation unit is sent to the pitch unit, which is the final step in distilling crude tar. More vacuum are applied in the pitch still to produce a second distillate stream known as heavy creosote. Creosote becomes more viscous at lower temperatures and eventually reaching semi-solid state at temperatures below 100°F. Both storage tanks and transporting vessels are heated.

The final bottoms stream is known as coal tar pitch and is extremely viscous even at temperatures of 300°F to 400°F. As it cools, it becomes solid and, at ambient temperatures, becomes brittle and exhibits crushing characteristics similar to coal. It is transported to customers as a hot liquid or as a cold solid.

The Houston Plant also blends coal tar distillation products with both asphaltic and coal tar materials to make a variety of products to meet our customer's demand. They are made on a batch basis usually by mixing in tanks. However, due to the viscosity of the materials and the intermediate treatment steps, they are unlikely to reach the biological unit.

(2) The following is a complete list of the raw materials and laboratory chemicals which are used at the Houston Plant that are not coal tar based. Those items marked with (*) are used in processes which do not generate waste water. Their introduction to the treatment system would be only as a result of a spill.

Petroleum Residual Oil
Process Coal - Bituminous
Talc
Hydrated Lime
Activated Carbon
Acetone
Quinoline
Toluene
Xylene
Hydrochloric Acid
Caustic Soda
Sulfuric Acid
Phosphoric Acid - Bionutrient
Glycerine

(3) The production process at the plant is only distillation and blending. Except for some commercial cleaners, there are no solvents, cleaners, or surface preparation agents which are in use at Houston.

There are a number of chemicals which are added to the boilers and cooling towers for various purposes. Since the blowdown from the boilers and cooling towers is to the treatment system these compounds may be in the waste stream. Material Safety Data Sheets are attached for the following compounds:

Nalco	7274	Amines			agriba.
Nalco	7201	Acrylic	Polymer		
Nalco	8365	Organic	Phosphoro	us	
Nalco	7309	Organic	Surfactan	ts	7.5
Nalco	7460	Hydrocar	bon Based	Anti-Fo	am

- (4) We have not, to date, wasted biological sludge nor do we intend to begin as long as the production level remains as is. The purpose of delisting at this time is to simplify the disposal of the excess sludge if and when it becomes necessary. At that time it is likely that the liquid sludge will be stabilized with dry material, e.g., cement kiln dust and landfilled.
- (5) The samples of waste biological sludge which are to be analysed will be collected by taking a grab sample off the recycle sludge line. The recycle sludge line transports the sludge which settles in the clarifier back to the aeration tank for reuse. Although the regulations specify composite sampling, this method is more suitable for activated sludge for the following reasons:
 - Biological activity will continue on samples taken early in the compositing period which may create a sludge of a different characteristic than the sludge which is actually in the system.

2. The sludge itself does not change over a 24-hour period. The sludge in our system has been there for a long time. There is no large production of sludge taking place at this time. Sampling by a composite technique will not make the sample more representative than a single grab sample taken during the day.

It should also be noted that the Houston Plant has 100,000 gallons of equalization capacity. The purpose of equalization is to smooth out the operation of the treatment system by reducing the variations in influent composition. This will further mitigate the need for composite sampling.

It is not expected that the characteristics of the waste would vary significantly over the year. The operations at the Houston Plant are not seasonal, but rather steady throughout the year. Thus the influent characteristics remain essentially the same. Neither does the operation of the treatment plant differ appreciably between winter and summer except in the amount of stormwater. The only change that is made is that during periods of extreme cold weather, steam may be introduced to maintain the basin temperature high enough to assure biological activity. The singluar factor that would influence treatment efficiency is the system temperature and we are able to maintain essentially the same temperature on a year around basis.

- (6) No sludge is generated at this time.
- (7) (provided with analytical package)
- (8) (provided with analytical package)
- (9) A schematic flow diagram of the biological treatment system is attached. The description is as follows:
 - a. Decantation Process wastewater is decanted to remove most of the oil before processing begins. By controlling the temperature in the decanting vessel at the optimum, most of the oil can be removed and returned to process.
 - b. Equalization The purpose of equalization is to smooth out the variations in influent wastewater to prevent upsets of the treatment system. The equalization tank that holds nearly seven days of wastewater on the average so that any pollutant or flow peaks in the influent wastewater can be eliminated.
 - c. API Separation Wastewater is introduced into the API Separator when the free oils are allowed to separate from the wastewater. Oils heavier than water settle to the

bottom and oils lighter than water float to the top. Both oil streams are removed and returned to process. The wastewater continues to oil extraction.

- d. pH Adjustment Biological treatment works best at a neutral pH. Since our wastewater is usually within that range the pH adjustment is an added precaution to insure pH compliance.
- e. Activated Carbon Addition Granulated activated carbon is added to the treatment process because experience has shown that it offers several advantages:
 - 1. It provides a site for the agglomeration of sludge particles which enhances settling.
 - 2. Activated carbon absorbs organics so if the treatment system becomes temporarily overloaded, the excess organics are absorbed onto the carbon particles.
 - The activated carbon works to reduce foaming in the treatment system and provides better oxygen transfer.
- f. Aeration The wastewater is introduced into the aeration tank where the biological activity takes place. The aeration tank is equipped with a surface aerator that creates turbulance and splashing. This causes the oxygen in the air to be absorbed in the water of the aeration tank. Recycled sludge from the clarifier is introduced to the aerator to provide microorganisms which consume the organics in the wastewater. The aeration tank discharges to the clarifier.
- g. Clarification In the clarification step the treated effluent and biological organisms which overflow from the aeration tank are separated into two streams. The clarifier provides a quiescent zone where the more dense sludge particles separate from the treated effluent. The clarifier also has a skimming mechanism in the case that oils or other floating debris may have been inadvertently introduced into the treatment system. The overflow from the clarifier goes to the outfall. The underflow which is biological sludge is returned to the aeration tank.
- (10.) (provided with analytical package.
- (11.) (provided with analytical package)

I hope that this submission will provide you with sufficient information to determine what, if any analytical work is required beyond that required in 40 CFR 260.22. If you have any questions, please call me at (412) 227-2207 so that I can expedite our response. We request that you review this information as soon as possible so that we can get on with the analytical work required for the delisting process.


"I certify under penalty of law that I have personally examined and am familiar with the information submitted in this demonstration and all attached documents and that, based on my inquiry of those individuals immediately responsible for obtaining the information, I believe that the submitted information is true, accurate and complete. I am aware there are significant penalties for submitting false information including the possiblity of fine and imprisonment."


Sincerely yours,

Jordan M. Dern, Manager

Environmental Regulatory Programs

JMD/s





Product

سا،	1	7	ኃ
#	· ')'		

SECTION 1 - PRODUCT IDENTIFICATION

Trade Name	Nalco 7274				_ Formula No	
Synonyms A	n aqueous B	lend of ami	nes			
				Chamles	_{Family} Organi	.c

SECTION 2 — HAZARDOUS INGREDIENTS

MATERIAL OR COMPONENT	*
Hydrazine	3

SECTION 3 — PHYSICAL PROPERTIES

Boiling Point, 760 MM HG	MoHing Solds Ireeze point 13 F
Specific Gravity (H ₂ O=1) 1.0 @ 60 F	Vapor Pressure 28 Torr @ 77°F
Vapor Demity (Air*1)	Solubility in H ₂ 0, % By Wt. Complete
% Volatiles By Vol. 30% @ 77°F	2.9 cps @ 77°F
Appearance and Odor Clear, colorless to yellow liquid	pH (neat) = 11.5

SECTION 4 - FLAMMABILITY AND EXPLOSIVE PROPERTIES

	(Test Method)	· Section Section	es in this star sin		7
> 200°F	(PMCC)				
Flammable	Limits in Air, % By Vol.		Lower	Upper	
Extinguishin	ng Media Dry chemical,	alcohol for	am.		•
1 The Co.	Fighting Procedures air supplied b	reathing a	paratus		
1	e and Explosion Hazard iberate NOx				

SECTION 5 - HEALTH HAZARD DATA

Threshold Limit Value

Hydrazine = 1.0ppm OSHA 1978 limit;

ACGIH TLV (1978) = 0.1ppm, NIOSH recommondation (1978) = 0.03ppm

Effects of Overexposure

Can cause eye and skin burns. May be harmful if absorbed through the skin. Vapors may cause lung and mucous membrane injury. Hydrazine is a suspect carcinogen.

EMERGENCY AND FIRST AID PROCEDURES

Even Immediately flush with water for a least 15 minutes. Call a physician.

sum Immediately flush with water for 15 minutes. Consult a physician.

insestion Give large amounts of water. Do not induce vomiting. Call a physician.

Inhalation Remove to fresh air. If not breathing, give artifical respiration, Oxygen. Consult a physician.

ECTION 6 - REACTIVITY DATA	
Stability: Stable 🖫 > Conditions to	Avaid
Materials to Availa ACIDS, OXI	dizing agents
Mazzrdous Decemposition Products NC	x, co ₂ , co
Hazardous Polymerization: Will Not Occur	
CTION 7 - SPILL OR LEAK PRO	OCEDURES
	Small and land land
Steps to Take in Case Material is Released o Water, wear amine cart	ridge respirator and prevent skin or eve
contact by wearing imp	ervious gloves, rubber boots, face chief
and chemical goggles.	For large spill wear self contained breathing
apparatus, slicker sui	t, rubber boots and gloves.
Waste Disposal Method No specia	l methods. Consult local, state, or federal
regulations for approp	riate compliances
regulations for approp	riate compliances.
regulations for approp	riate compliances.
regulations for approp	
CTION 8 — SPECIAL PROTECTION	ON INFORMATION
CTION 8 — SPECIAL PROTECTION	ON INFORMATION One when used in closed system. Cartridge
CTION 8 — SPECIAL PROTECTION No Type of Respiratory Protection Required To	ON INFORMATION one when used in closed system. Cartridge espirator when opening drum or when small
CTION 8 — SPECIAL PROTECTION No Type of Respiratory Protection Required Telephone	ON INFORMATION one when used in closed system. Cartridge espirator when opening drum or when small eaks develop.
CTION 8 — SPECIAL PROTECTION No Type of Respiratory Protection Required To Letter Ventilation: Local Exhaust : Mechanica	ON INFORMATION One when used in closed system. Cartridge espirator when opening drum or when small eaks develop. (General) (General) (Special (Special))
CTION 8 - SPECIAL PROTECTION No Type of Respiratory Protection Required re 16 Ventilation: Local Exhaust : Machanics Rubber when op Protective Gloverdrum or if lea	ON INFORMATION One when used in closed system. Cartridge espirator when opening drum or when small eaks develop. (General)
CTION 8 - SPECIAL PROTECTION No Type of Respiratory Protection Required re 16 Ventilation: Local Exhaust : Machanics Rubber when op Protective Gloverdrum or if lea	ON INFORMATION One when used in closed system. Cartridge espirator when opening drum or when small eaks develop. (General)
CTION 8 - SPECIAL PROTECTION No Type of Respiratory Protection Required re le Ventilation: Local Exhaust : Machanics Rubber when op Protective Glovesdrum or if les develop. Other Protective Equipment Full re	ON INFORMATION One when used in closed system. Cartridge espirator when opening drum or when small eaks develop. (General) A Special (Specify) Other (Specify) Denimy Face shield and goggles when the second opening drum or when leaks develop. Orotection suit and self-contained breathing
CTION 8 — SPECIAL PROTECTION No. Type of Respiratory Protection Required re- le Ventilation: Local Exhaust : Machanics Rubber when op Protective Glovedrum or if les develop. Other Protective Equipment Full paratus for large spi	ON INFORMATION One when used in closed system. Cartridge espirator when opening drum or when small eaks develop. (General) **Dispectal (Special)** Other (Special)** Denily Face shield and goggles when the second suit and self-contained breathing this. Protective equipment not necessary
CTION 8 - SPECIAL PROTECTION No. Type of Respiratory Protection Required re- le Ventilation: Local Exhaust : Machanics Rubber when op Protective Glovedrum or if les develop. Other Protective Equipment Full re-	ON INFORMATION one when used in closed system. Cartridge espirator when opening drum or when small eaks develop. (General) A Special (Specify) Other (Specify) pening Face shield and goggles when aks Eye Fretetten opening drum or when leaks develop. Orotection suit and self-contained breathing alls. Protective equipment not necessary of closed system.
CTION 8 — SPECIAL PROTECTION Type of Respiratory Protection Required respiratory Protection Required responses Ventilation: Local Exhaust : Mechanical Rubber when operative Giovendrum or if lead develop. Other Protective Equipment Full paparatus for large spilluring normal operation	ON INFORMATION one when used in closed system. Cartridge espirator when opening drum or when small eaks develop. (General) A Special (Specify) Other (Specify) pening Face shield and goggles when aks Eye Protection opening drum or when leaks develop. Orotection suit and self-contained breathing alls. Protective equipment not necessary of closed system.
CTION 8 — SPECIAL PROTECTION Type of Respiratory Protection Required respiratory Protection Required responses Ventilation: Local Exhaust : Machanical Rubber when operative Gloverdrum or if lead develop. Other Protective Equipment Full paparatus for large spin suring normal operation. CTION 9 — SPECIAL PRECAUTION Handling and Storage Procaution Store	ON INFORMATION One when used in closed system. Cartridge espirator when opening drum or when small eaks develop. (General) Special (Specify) Other (Specify) Denily Face shield and goggles when aks Drotection opening drum or when leaks develop. Orotection suit and self-contained breathing alls. Protective equipment not necessary of closed system. ONS in cool, dry area. Keep container closed
CTION 8 — SPECIAL PROTECTION Type of Respiratory Protection Required respiratory Protection Required responses Rubber when operative Guivendrum or if lead develop. Other Protective Equipment Full proparatus for large spiral programment operation. CTION 9 — SPECIAL PRECAUTION. Handling and Storage Procaution Stores igntly when not in use	ON INFORMATION one when used in closed system. Cartridge espirator when opening drum or when small eaks develop. (General) Special (Specify) Other (Specify) oening Face shield and goggles when aks develop. Orotection suit and self-contained breathing ells. Protective equipment not necessary of closed system. ONS in cool, dry area. Keep container closed one of contact skin, eves or clothing
CTION 8 — SPECIAL PROTECTION Type of Respiratory Protection Required respiratory Protection Required responses Rubber when operative Guivendrum or if lead develop. Other Protective Equipment Full proparatus for large spiral programment operation. CTION 9 — SPECIAL PRECAUTION. Handling and Storage Procaution Stores igntly when not in use	ON INFORMATION One when used in closed system. Cartridge espirator when opening drum or when small eaks develop. (General) Special (Specify) Other (Specify) Denimy Face shield and goggles when aks develop drum or when leaks develop. Orotection suit and self-contained breathing alls. Protective equipment not necessary of closed system. ONS in cool, dry area. Keep container closed
CTION 8 — SPECIAL PROTECTION Note Type of Respiratory Protection Required relation: Local Exhaust Rubber when operative Glovesdrum or if lead develop. Other Protective Equipment Tull paparatus for large spilluring normal operation. CTION 9 — SPECIAL PRECAUTION. Handling and Storage Procaution Store ightly when not in use the second control of the second contro	ON INFORMATION One when used in closed system. Cartridge espirator when opening drum or when small eaks develop. (General) [In Special (Special)] Other (Special) Dening Face shield and goggles when siks Eve Protection opening drum or when leaks develop. Protection suit and self-contained breathing alls. Protective equipment not necessary a of closed system. ONS in cool, dry area. Keep container closed and contact skin, eyes or clothing. thes before reuse. Discard containinated
CTION 8 — SPECIAL PROTECTION Type of Respiratory Protection Required relation: Local Exhaust : Machanics Rubber when operative Glovesdrum or if lead develop. Other Protective Equipment Full relations for large spining normal operation. CTION 9 — SPECIAL PRECAUTION Handling and Storage Procaution Store igntly when not in use the second store and launder clothoes.	ON INFORMATION One when used in closed system. Cartridge espirator when opening drum or when small eaks develop. I (General)
CTION 8 — SPECIAL PROTECTION Type of Respiratory Protection Required relation: Local Exhaust : Machanics Rubber when operative Glovesdrum or if lead develop. Other Protective Equipment Full paparatus for large spilluring normal operation. CTION 9 — SPECIAL PRECAUTION Handling and Storage Precaution Store ightly when not in use lemove and launder clothoes.	ON INFORMATION One when used in closed system. Cartridge espirator when opening drum or when small eaks develop. (General) I special (Specify) Other (Specify) Denils Face shield and goggles when aks evelop. Strotection suit and self-contained breathing alls. Protective equipment not necessary of closed system. ONS in cool, dry area. Keep container closed on the contact skin, eyes or clothing. these before reuse. Discard containinated

Corporate Title Toxicolog

An aqueous solution of an acrylic polymer Chemical Panilip ION 2 — HAZARDOUS INGREDIENTS MATERIAL OR COMPONENT None ION 3 — PHYSICAL PROPERTIES Illing Point, 740 MM HQ 250F Freeze Point 250F Vapor Prinsure 13 6 60P Per Denality (Air=1) Solublity in H20, % By Wt. Soluble 30 cps @ 77°F John 4 — FLAMMABILITY AND EXPLOSIVE PROPERTIES IN Polici (Test Method) None Insulability in Air, % By Vol. Lower Uppe List yellow liquid pH (neat) = 4.8 pH (1% sol'n) = 5.8 Insulability in Air, % By Vol. Lower Uppe List yellow liquid pH (neat) = 4.8 pH (1% sol'n) = 5.8 Insulability in Fighting Precedures Lone Mone established for the product. State of Overspeare Lay cause irritation with prolonged contact. Lagency And Pirst Aid Procedures List yellow limits with water for 15 minutes. Call a physician. A cash thoroughly with soap and water. John on thinduce vomiting. Give water. Call a physician.	rmula No
ION 2 — HAZARDOUS INGREDIENTS MATERIAL OR COMPONENT None ION 3 — PHYSICAL PROPERTIES IIIIng Point, 780 MM HG 250F Vapor Pressure 13 @ 600F per Dendity (M201) Voictilies By Vot. 30 cps @ 770F Desarrance and Odor Light yellow liquid pH (neat) = 4.8 pH (1% sol'n) = 5.8 ION 4 — FLAMMABILITY AND EXPLOSIVE PROPERTIES Solve turns in Air, % By Vot. Lewer Upper Lingularing Media Jone Lone	
ION 2 — HAZARDOUS INGREDIENTS MATERIAL OR COMPONENT None ION 3 — PHYSICAL PROPERTIES IIIIng Point, 780 MM HG 250F Vapor Pressure 13 @ 600F per Dendity (M201) Voictilies By Vot. 30 cps @ 770F Desarrance and Odor Light yellow liquid pH (neat) = 4.8 pH (1% sol'n) = 5.8 ION 4 — FLAMMABILITY AND EXPLOSIVE PROPERTIES Solve turns in Air, % By Vot. Lewer Upper Lingularing Media Jone Lone	Organic
None ION 3 — PHYSICAL PROPERTIES Illing Point, 740 MM HQ Selfile drawity (H ₂ O=1) 1.3 @ 600 F POP Density (Air=1) Solubility in H ₂ O, % By Wit. Soluble Voiatilitie By Vot. Jone (Jone) Jone	
None ION 3 — PHYSICAL PROPERTIES Illing Point, 740 MM HQ Selfile drawity (H ₂ O=1) 1.3 @ 600 F POP Density (Air=1) Solubility in H ₂ O, % By Wit. Soluble Voiatilitie By Vot. Jone (Jone) Jone	
ION 3 — PHYSICAL PROPERTIES Iting Point, 786 MM HQ 250F Solubility (H20=1) 13 @ 600F Per Density (Ar=1) Volatifies By Vol. 30 cps @ 77°F Light yellow liquid ION 4 — FLAMMABILITY AND EXPLOSIVE PROPERTIES sh Point (Test Method) ION 6 Impulsifies In Air, % By Vol. Lower Upper Method Ione In a physicale Ione In a physicale Ione established for the product, Ione established for the p	
ION 3 — PHYSICAL PROPERTIES Iting Point, 788 MM Hd 250F Vapor Freeze Point 250F Vapor Freeze Notable 30 cps @ 770F Soluble 30	
Freeze Point 25°F 25°F 25°F Napor Pressure 13 @ 60°F per Dansity (Air=1) Solubility in H20, % By Wt. Soluble Volatilies By Vol. Pearance and Oder Light yellow liquid pH (neat) = 4.8 pH (1% sol'n) = 5.8 ION 4 — FLAMMABILITY AND EXPLOSIVE PROPERTIES Sh Point (Test Method) Jone Immable Limits in Air, % By Vol. Lewer Uppe Linguishing Media Not applicable Ione	
Freeze Point 25°F 25°F 25°F Napor Pressure 13 @ 60°F per Dansity (Air=1) Solubility in H20, % By Wt. Soluble Volatilies By Vol. Pearance and Oder Light yellow liquid pH (neat) = 4.8 pH (1% sol'n) = 5.8 ION 4 — FLAMMABILITY AND EXPLOSIVE PROPERTIES Sh Point (Test Method) Jone Immable Limits in Air, % By Vol. Lewer Uppe Linguishing Media Not applicable Ione	
Freeze Point 25°F 25°F 25°F Napor Pressure 13 @ 60°F per Dansity (Air=1) Solubility in H20, % By Wt. Soluble Volatilies By Vol. Pearance and Oder Light yellow liquid pH (neat) = 4.8 pH (1% sol'n) = 5.8 ION 4 — FLAMMABILITY AND EXPLOSIVE PROPERTIES Sh Point (Test Method) Jone Immable Limits in Air, % By Vol. Lewer Uppe Linguishing Media Not applicable Ione	
Freeze Point 25°F 25°F 25°F Napor Pressure 13 @ 60°F per Dansity (Air=1) Solubility in H20, % By Wt. Soluble Volatilies By Vol. Pearance and Oder Light yellow liquid pH (neat) = 4.8 pH (1% sol'n) = 5.8 ION 4 — FLAMMABILITY AND EXPLOSIVE PROPERTIES Sh Point (Test Method) Jone Immable Limits in Air, % By Vol. Lewer Uppe Linguishing Media Not applicable Ione	
Freeze Point 25°F 25°F 25°F Napor Pressure 13 @ 60°F per Dansity (Air=1) Solubility in H20, % By Wt. Soluble Volatilies By Vol. Pearance and Oder Light yellow liquid pH (neat) = 4.8 pH (1% sol'n) = 5.8 ION 4 — FLAMMABILITY AND EXPLOSIVE PROPERTIES Sh Point (Test Method) Jone Immable Limits in Air, % By Vol. Lewer Uppe Linguishing Media Not applicable Ione	
250F Vapor Pressure 1.3 @ 60°F per Demility (Air=1) Volatifies By Vol. Solubile Volatifies By Vol. Solubile 30 cps @ 77°F Ight yellow liquid pH (neat) = 4.8 pH (1% sol'n) = 5.8 ION 4 — FLAMMABILITY AND EXPLOSIVE PROPERTIES sh Point(Test Method) None Impulshing Media Not applicable Ione Ion	
.13 @ 60°F per Density (Air=1) Solubility in H20, % By Wt. Soluble Voiatifies By Vol. Joans and Odor John 4 — FLAMMABILITY AND EXPLOSIVE PROPERTIES Sh Point (Test Method) Jone Impulshing Media Not applicable List Fire Fighting Procedures Jone ION 5 — HEALTH HAZARD DATA Teshoid Limit Value Jone established for the product. Sects of Overexposure Lay Cause irritation with prolonged contact. Ligency And Pirst Aid Procedures Light yellow liquid pH (neat) = 4.8 pH (1% sol'n) = 5.8 Light yellow liquid pH (neat) = 4.8 pH (1% sol'n) = 5.8 Lower Uppe Uppe Lower Uppe Uppe Lower Up	
per Density (Air=1) Solubility in H20, % By Wt. Soluble 30 cps (8 77°F pastance and Odor Light yellow liquid pH (neat) = 4.8 pH (1% sol'n) = 5.8 ION 4 — FLAMMABILITY AND EXPLOSIVE PROPERTIES an Point(Test Method) Jone Impulsiving Media Jot applicable Iot applicable Iotal Fire Fighting Procedures Jone ION 5 — HEALTH HAZARD DATA Pershold Limit Value Ione established for the product. Sects of Overexposure Lay cause irritation with prolonged contact. Ideancy and Pirst Aid Procedures Insulation with water for 15 minutes. Call a physician. Josh thoroughly with soap and water.	
Pasarance and Odor John Sparance and Class of the Sparance and Sparance	
paarance and Odor ight yellow liquid pH (neat) = 4.8 pH (1% sol'n) = 5.8 ION 4 — FLAMMABILITY AND EXPLOSIVE PROPERTIES an Point (Test Method) None Immable Limits in Air, % By Vol. Lower Uppe Inequishing Media Not applicable Iola Fire Fighting Procedures Jone ION 5 — HEALTH HAZARD DATA reshold Limit Value Ione established for the product, sets of Overexposure Lay cause irritation with prolonged contact. IGENCY AND FIRST AID PROCEDURES I Lish with water for 15 minutes. Call a physician. In Cash thoroughly with soap and water.	
ight yellow liquid pH (neat) = 4.8 pH (1% sol'n) = 5.8 ION 4 — FLAMMABILITY AND EXPLOSIVE PROPERTIES sh Point (Test Method) Jone	Viscosity
ION 4 — FLAMMABILITY AND EXPLOSIVE PROPERTIES sh Point (Test Method) Jone Immable Limits in Air, % By Vol. Lewer Uppe Identifying Media Jot applicable Identifying Procedures Jone ION 5 — HEALTH HAZARD DATA Institute Ione established for the product. Ione established for the product. Identify Cause irritation with prolonged contact. Identify And Pirst Aid Procedures In the World American Address Call a physician. In the Cash of Control of the Call a physician. I ash thoroughly with soap and water. In the Cash of Control of the Call a physician. I ash thoroughly with soap and water.	
Not applicable total Fire Fighting Procedures None Bone BON 5 — HEALTH HAZARD DATA Tesheld Limit Value None established for the product. Sects of Overexposure May cause irritation with prolonged contact. Takency And First Aid Procedures Bush with water for 15 minutes. Call a physician. The section of the product of the procedures of the proce	
Ione usual Fire Fighting Procedures Jone UN 5 — HEALTH HAZARD DATA reshold Limit Value Jone established for the product, sets of Overexposure Lay cause irritation with prolonged contact. REMINISTRATE PROCEDURES Is lush with water for 15 minutes. Call a physician. In the content of the product of the product of the procedures of	
Jone Jone Jone Jone Jone Jone Jone Jone	
Jone ION 5 — HEALTH HAZARD DATA reshold Limit Value Ione established for the product. sets of Overexposure lay cause irritation with prolonged contact. Identity and First Aid Procedures In the last with water for 15 minutes. Call a physician. In the last thoroughly with soap and water. Settler is a set of the product.	
ION 5 — HEALTH HAZARD DATA reshold Limit Value Jone established for the product. acts of Overexposure Lay cause irritation with prolonged contact. Reshord AND FIRST AID PROCEDURES Lush with water for 15 minutes. Call a physician. The Cash thoroughly with soap and water. Sestion	
lone established for the product. acts of Overexposure lay cause irritation with prolonged contact. taking and pirst aid procedures lush with water for 15 minutes. Call a physician. (ash thoroughly with soap and water.	
lone established for the product. lay cause irritation with prolonged contact. Idency and First aid Procedures Lush with water for 15 minutes. Call a physician. Vash thoroughly with soap and water.	
lay cause irritation with prolonged contact. IGENCY AND FIRST AID PROCEDURES Lush with water for 15 minutes. Call a physician. Vash thoroughly with soap and water.	
laency and First aid Procedures Lush with water for 15 minutes. Call a physician. Vash thoroughly with soap and water.	
lush with water for 15 minutes. Call a physician. (ash thoroughly with soap and water.	
lush with water for 15 minutes. Call a physician. (ash thoroughly with soap and water.	
lush with water for 15 minutes. Call a physician. (ash thoroughly with soap and water.	
lush with water for 15 minutes. Call a physician. (ash thoroughly with soap and water.	
ash thoroughly with soap and water.	
estion	
o not induce vomiting. Give water. Call a physician.	
AN A STATE OF THE PARTY OF THE	

Transport-Plus 7201

Product

	Unstable His to Aveid		one to Avoid						
		Alumin							
		Alumin	A Company						
Hazard			um, coppe	er, copper a	alloys, mile	d steel, nick	el, neopren	e	
	ous Decempositi	on Producti	None						
Hazard	ous Polymerizati		ot Occur 🔲 X	nditions to Avo	ld				
TION	7 - SPILL	OR LEA	K PROCED	OURES					
Steps te	Take in Case Ma	terial is Rel	essed or Spille	<u>Cont</u>	ain with al	bsorbent ma	terial.		
			a substitution						
							<u>역 발범</u> 보니다. 기원 보통하다.		•
Waste Di	isposel Methed	No s	<u>pecial me</u>	thod. Con	sult local,	state and fe	ederal regu	lations	•
for	appropriat	<u>e dispos</u>	al	• • • • • • • • • • • • • • • • • • • •		aw in the			
TION	8 - SPECIA	L PROT	ECTION IN	VEORMATI	ON				
Type of	Respiratory Prote	ection Requ	ired <u>No</u>	ne normall	y required				
/entilati	on: Local Exhau	st □; Me	chanical (Gane	ral) 🔲; Specia	st (Specify)	Othe	r (Specify)		
		Rubber							
				Eye	Protection	Goggles			
ther Pro	itective Equipme	nt <u>N</u>	one						
TION S	9 - SPECIAI	PRECA	UTIONS						13 M N
angiing .	and Storage Prec	ution	Keep ir	om treezin	g. Recom	mended stor	rage tempe	rature ra	ange
_is_5	0 - 120°F.					er Stypelliger in Secondary (1937)			* 1.11
l diserva Literar									
de la Company									
		io net ti	ike Intern	ally. Avoi	d eye and	prolonged sl	din contact		
									i jar

Product

		=	
			100
٠		LO ROAD DOAK BROOK.	
	Ü	=	1.0
1.	u	•	
5	-	ň	1.1
	_	_	
			1.0
100	_	-	
	EMICAL	-	
4	a		100
	•	-	
j i	••	◂	1.00
	u	~	
	_	u	100
	-	_	· .
		-	
	•	~	
	~	_	
100	_	•	
		Ä	
	ш	J	10 m
	_	•	
	U	_	
	I	•	S. S.
	_	٠.	*
		-	,
	ш	ш	
	_	-	
		u.	
	_	æ	
	п	-	
	•	ш	
		-	
	71	_	
	•	Ξ	
		_	
٠.	_	m	 In the second of the second of
200		-	
	•	-	133
	ч.	7	
	-	~	
14.0	NALCO	2901 BUTTERFIEI	
	~	ě.	
96	_		4.1
	_ /		

Trade Name Naico 8365	
	Formula Na.
Synenyme An aqueous blend of organic p	olymers and organo phosphorous compounds
	Chemical Family Organic
ECTION 2 — HAZARDOUS INGREDIENTS	
MATERIALOR	COMPONENT
Entire product is alkaline	
ECTION 3 — PHYSICAL PROPERTIES	
Boiling Point, 760 MM HG	Freeze Point
Specific Gravity (H ₂ O=1)	Vapor Pressuro
1.19 ± 0.02 @ 70°F Vapor Density (Air=1)	Solubility in H ₂ O, % By Wt.
	Soluble
% Volatiles By Vol.	Viscosity
Appearance and Odor	12±4 cps @ 70°F
Yellow liquid, mild organic odor pH	1. (3 ± .3)
ECTION 4 - FLAMMABILITY AND EXPLOSIV	/E PROPERTIES
Flash Point (Test Method)	<u>. 1987 - Angele Barrier, and Angele Barrier, </u>
None	
Flammable Limits in Air, % By Vol.	Lower and the Control of the Control
Extinguishing Media	
CO2, dry chemical, alcohol foam, water f	og
None	
Unusual Fire and Explosion Hazard	
Unusual Fire and Explosion Hazard None	
Unusual Fire and Explesion Hazard None	
Unusual Fire and Explesion Hazard None	
Unusual Fire and Explosion Hazard None ECTION 5 — HEALTH HAZARD DATA Threshold Limit Value None established for the product.	
Unusual Fire and Explosion Hazard None ECTION 5 — HEALTH HAZARD DATA Threshold Limit Value None established for the product. Effects of Overexposure	
Unusual Fire and Explosion Hazard None ECTION 5 — HEALTH HAZARD DATA Threshold Limit Value None established for the product.	
Unusual Fire and Explosion Hazard None ECTION 5 — HEALTH HAZARD DATA Threshold Limit Value None established for the product. Effects of Overexposure May cause severe irritation due to alkalin	Ĭ.
Unusual Fire and Explosion Hazard None ECTION 5 — HEALTH HAZARD DATA Threshold Umit Value None established for the product. Effects of Overexposure May cause severe irritation due to alkalin	ity
Unusual Fire and Explosion Hazard None ECTION 5 — HEALTH HAZARD DATA Threshold Limit Value None established for the product. Effects of Overexposure May cause severe irritation due to alkalin EMERGENCY AND FIRST AID PROCEDURES	

Naico 8365

	111			1.5
	Ш	340		
	_	Ξ		
	_	_		٠.
	I	~		
	-			
		_		
		-		
	Ü	*12		
	-	=		
			- 1	
	_	_	10.0	
	•	-		
3	0			
	•	-		
		TEFFE		
	77	_		
	_	_		
	U	=		
	AL	200100		
		-		
	_	_		
		-		
	_	-		٠.
	•	=		
	•	_		
		=	٠.	
	-	_	/	- 1
	•	-		
	Z			
	· -			
ċ				
,	_			
	-	-		
- 4	А-ч			
		- 24		
	-	•		
	2.5	. T.		
٠,	-	_	10.0	٠.
	-	•		
٠.,		•	٠.	1.5
		-	•	1.1

ECTION 6 - REACT	IVITY DATA			
Stability: Stable 🖾 Unstable 🔲	Canditions to Avoid			
Meterials to AvoidAC	elds			
Hazardeus Dosempeşitica	Products None			
Nezardous Polymerization	Will Not Occur 🗗 May Occur 🔲 Condition	s to Avoid		
CTION 7 - SPILL O	R LEAK PROCEDURE	S		
Steps to Take in Case Mete	urisi is Released or Spilled	Contain with ab	sorbent materi	al.
	Consult local, state	and federal res	ulations for ap	propriate
Weste Dispessi Method				
disposal.				
CTION 8 - SPECIAL	PROTECTION INFO	RMATION		
Type of Resolutions Prote	None None			
	st 🔲 ; Moshanizai (General) [Security)
Protoctive GlovesRU	bber, gauntlets	Eye Protection	Goggies	
Other Pretective Equipmen	Impervious apror			
CTION 9 — SPECIAL	.PRECAUTIONS			
	Do not take i	nternaliv. Avo	id eve and skin	contact. Remove
Handling and Sterage Proce				
and launder cont	aminated clothing be	iore reuse.		
Other Procesutions No	one			
		Сол	orate	
Prepared By	Von Stewar	Title Tox	Cologist	Date [2/8/8]

Nalco 7309

SECTION 1 -	PRODUCT IDENTIFICATION		
Trade Name	Nalco 7309	Formula No	
Synonymt	Oil remover/degreaser		
			Organic
SECTION 2 -	HAZARDOUS INGREDIENTS		
	MATERIAL OR COMPONENT		

MATERIAL OR COMPONENT		
None		
		
		(setter

Solling Polet, 760 MM HG	Melting Polat
Seedlike Gravity (H20=1) 1.02 @ 60°F	Vaper Fraudis
Vapor Domity (Air=1)	Solubility in MgO, % by Wt. Completely
% Velatiles By Vel.	Evaporation Rate (Buty) Acetato-1)
Clear liquid, odorless pH (neat)= 6.4	

SECTION 4 - FLAMMABILITY AND EXPLOSIVE PROPERTIES

Fluid Point (Test Mothes) None (PMCC)	
Flammsbie Limits in Air, % By Yel.	- Vertical de la constant de la cons
Extinguishing Media CO ₂ , dry chemical, water fog	
Special Fire Fighting Procedures None	
Unusual Fire and Explosion Mazard None	

Taresneid Limit Value	
None established for the product.	
Effects of Oversupesson Possible skin and eye irritation.	
EMERGENCY AND FIRST AID PROCEDURES Eyes Wash with water for 15 minutes. Call a physician.	
Skin Wash the plenty of water.	
Induce vomiting. Give water. Call a physician.	
Inhelation Treat symptomatically.	

Product Naico 7309

ECTION 6 — RE	EACTIVITY DATA
Stability: Stable United	
Materials to Aveld	None
Hazardoùs Dotom	
Hezardous Palymo	rigation: Will Not Cocur 3 May Cocur C Conditions to Avoid
	May Occur Conditions to Avoid
CTION 7 - SPI	ILL OR LEAK PROCEDURES
Stees to Yake in Ca	the Material is Released or Spilled Wash down with water.
Waste Disposel Met	No special method.
TION 8 - SPE	CIAL PROTECTION INFORMATION
Type of Respiratory	Protection Required None normally required
Ventilistien: Local	Enhaust : Mechanical (General) : Special (Specify)Other (Specify)
Protective Gleves	Rubber Eye Pretieties Safety goggles
Other Pretective Equ	ulpment None
TION 9 - SPE	CIAL PRECAUTIONS
Handling and Sterag	Presiden Keep container closed when not in use.
uiner Processions	Do not take internally. Avoid eye and skin contact.
	성하는 것이 되었다. 그는 것이 되는 사람들은 사람들에게 되는 것이 없는 것이 없는 것이 되었다. 그런 것이 되었다는 것이 없는 것이 없는 것이다. 사용하는 사용하는 사용하는 것이 되었다. 그런 것이 되었다. 사용하는 사용하는 것이 되었다. 사용하는 것이 되었다.
	Corporate
Prepared By	Title Corporate Toxicologist Date 4/8/82

Similar to Form OSHA-20

EMERGENCY TELEPHONE NUMBER _ 13121 020.1510

Na1co 7460

Product

- 0	2
	70 : OV
-	_
	- :
	0
Σ	-
	4
Ш	C
	C
_	
I	0
	40.00
ט	<u>.</u>
	=
	LL.
	Œ
0	īie
U	TTGAF
	_
	m
ି ଏ	5
	<u> </u>
- 7	n
Z	Ω (V

Trade Name_	Nalco 7460			For	mula No		
	A hydrocarbon	based antifo	am				
				Chemical Family	Organi	C	
050510110	// A 7 A D D O L / O / D / O D						

MATERIAL OR COMPONENT	•
Petroleum Distillate	95
	7.
	. v = v = v = v = v = v = v = v = v = v

SECTION 3 - PHYSICAL PROPERTIES

Boiling Point, 760 MM HG	Melting Point
Specific Gravity (H ₂ O=1) 0.85 @ 70 F	Vapor Pressure
Vapor Demity (Air=1)	Solubility in H ₂ O, % By WL Insoluble
% Volatiles By Vol.	Evaporation Rate (Butyl Acetate=1)
Appearance and Odor Opaque tan liquid with hydrocarbor	odor

SECTION 4 - FLAMMABILITY AND EXPLOSIVE PROPERTIES

>350°F	nt (Test Met (COC)	hod)									
		Air, % By Vo	1.		Lower			Upper			
Water,			chemical			Maria de 1900. Maria de 1900.					
Wear a	ire Fighting air su	pplied	rescue	equipm	ent in	enclos	ed are	as.	Cool	exposed	•
None	ire and Exp	losion Hazar					C	ontai	ner w	ith wat	er

SECTION 5 - HEALTH HAZARD DATA

Threshold Limit Value
None for product. Oil mist = 5 mg/m
Effects of Overexposure-
Causes skin and eye irritation expecially upon repeated or prolonged
contact.
EMERGENCY AND FIRST AID PROCEDURES Syes
Flush with water for at least 15 minutes. Call a physician.
Wash with mild soap and rinse with plenty of water.
Ingestion in the state of the s
Do not induce vomiting. Call a physician.
Remove to safety. treat symptomatically.

Nalco 7460

SECTION 6 - REACTIVITY DATA

	7		•
	=	۲.	- 1
	•		
	-		
: •	Ξ		
	·		
-	Ci Ci		
	2.1	11.	. "
_	uş		
•		. S.	
A	1	٠.	
A.A.	-	7	
	▾		
•		٠.	
-	•		
		٠,٠	
1.67			

Stability: Stable 🔯 Cond	ditions to Avoid
Materials to Avoid Stror	ng oxidants
Mazardous Decomposition Frodu	ucts CO in case of incomplete combustion
	H Not Occur. X y Occur C Conditions to Avoid
ECTION 7 — SPILL OR LE	AK PROCEDURES
Steps to Take in Case Material is	Released or Spilled Contain on absorbent material
Waste Disposal Method LIIU	cinerate absorbed material. Keep petroleum product
out of streams a	ind waterways.
ECTION 8 - SPECIAL PRO	OTECTION INFORMATION
Type of Respiratory Protection Re	Required Normally not needed
Ventilation: Local Exhaust [];	Mechanical (General) : Special (Specify) Other (Specify)
Protective Gleves Rubber	그렇게 살아 그렇는 하를 잃었을까? 그는 말이 그렇게 하는 말이 하는 말이 되었다.
Other Protective Equipment	Oil imprevious apron
ECTION 9 — SPECIAL PRE	CAUTIONS CONTROL OF THE SECOND CONTROL OF TH
Handling and Storage Procession	
cool area: Avoi	d eye and skin contact. Avoid breathing aerosol o
mist.	
Other Precautions Laune	der contaminated clothing before reuse.

Corporate Toxicologist

8-11-80

Date

KOPPERS

October 4, 1983)

US EPA Region VI 1201 Elm Street Dallas, Texas 75270



The owner of the facility is:

Koppers Co., Inc. Koppers Bldg. Pittsburgh, Pa. 15219

?. The Address of the facility is:

Koppers Co., Inc. 0.M.G. Houston, Texas 77213 713/453-5446

- The incident occurred September 22, 1983 at 6:30 AM.
- 4. The incident consisted of a steam explosion in T-301 and a spill of 30,760 gallons of Refined Chemical Oil.
- 5. There were no injuries.
- 6. The most serious threat to human health was that the material could have hit a flame source and ignited causing a serious fire. In addition to the fire threat, Refined Chemical Oil contains coal tar derivatives and phenolic compounds that could have reached the Houston Ship Channel and been detrimental to the water quality had the spill plan not been followed.
- 7. We currently estimate that 400 cubic yards of oil saturated dirt will be removed and disposed of at the Browning-Ferris/Cecos International Calcasieu Disposal Facility, West Lake, La. Facility # LAD000618256.

J. A. Carnes

(1) 00 80800 mg